
WHBS 95 LM K

12NC: 859991566130

GTIN (EAN) code: 8003437236341







- Maximum noise level 65 dBA
- Noise Level (min. max.): 57-65 dBA
- Air Flow (min. max.): 302, 428 m3/h
- Maximum extraction rate: 428 (m3/h)
- Energy class D
- Extraction / Recirculation Rate 432 / 155 m3/h
- 2 LED, 6 W lamps
- 1 x 140 W motor
- Mechanical Buttons
- 3 Washable aluminium filters
- Grease Filtering Efficiency Class: C
- Lighting Efficiency Class: D
- Fluid Dynamic Efficiency Class: E
- Operating Mode: Air extraction, Recirculating air
- Inox Finishing
- 1 Motor
- Motor Power: 140 W

Whirlpool wall mounted cooker hood - WHBS 95 LM K

This Whirlpool wall mounted Cooker Hood features: black color. Dishwasher-safe, washable aluminium grease filters. LED lights for ideal lighting. An outstanding cooker extractor fan, ensuring a fresh, grease-free cooking environment. Between 60cm and 90cm wide appliance.



LED lighting

Increased energy and cost efficiency. The LED lighting system lasts 10 times longer than traditional bulbs and uses 90% less energy.



Flexible Installation

Flexible installation options. This Whirlpool Hood can be operated in either Ducted or Recirculated mode (filter needed), so you can enjoy complete freedom when designing your kitchen.



Mechanical control

Effortless control. This Whirlpool Hood includes an analogue control interface designed for simplicity and ease-of-use.



Wall-mounted installation

Wall-mounted installation. This wall-mounted Whirlpool Hood is a breeze to install.



Total annual energy consumption

Ideal performance, outstanding savings. Whirlpool Hoods are designed to provide exceptional results, while reducing energy costs.



TIMER

Perfect timing. This Whirlpool Hood includes an intuitive timer, for added convenience.



2 lights

Perfect lighting. This Whirlpool Hood features two integrated lights, providing ideal illumination, so you'll always be able to see what's cooking.



Energy class D

This is an Energy Class D appliance.

WHBS 95 LM K

12NC: 859991566130

GTIN (EAN) code: 8003437236341



Colour body Material body Colour chimney Inox Material chimney Stainless steel Typology Wall-mounted Installation type Wall-mounted Installation type Wall-mounted Type of control Mechanical Type of control Mechanical Type of control Mechanical Type of control Integrated motor in hood chimney Coperating Mode Convertible Electrical connection rating (W) Current (A) Voltage (V) Frequency (Hz) Frequency (Hz) Length of Electrical Supply Cord (cm) Flugt type Schuko Chimney height (mm) Height of product, without chimney (mm) Height of product, without chimney (mm) Without of the product Minimum niche height Minimum niche height Minimum niche width Minimum niche wi	MAIN FEATURES		
Material body Stainless steel Colour chimney Inox Material chimney Stainless steel Typology Wall-mounted Installation type Wall-mounted Type of control Mechanical Type of control Mechanical Type of control settings - Decor panel options N/A Motor location Integrated motor in hood chimney Operating Mode Current (A) 1,6 Current (B) 1,6 Current (Ca) 1,	Product group	Hood	
Colour chimney Inox Material chimney Stainless steel Typology Wall-mounted Installation type Wall-mounted Type of control Mechanical Type of control settings - Decor panel options N/A Motor location Integrated motor in hood chimney Operating Mode Convertible Electrical connection rating (W) 146 Current (A) 1,6 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) - Height of product, without chimney (mm) 0 Height of the product 898 Depth of the product 450 Minimum niche height 0 Minimum niche width 0 Niche depth 0	Colour body	Black	
Material chimney Typology Wall-mounted Installation type Wall-mounted Type of control Mechanical Type of control Mechanical Type of control Settings Decor panel options N/A Motor location Integrated motor in hood chimney Operating Mode Convertible Electrical connection rating (W) 146 Current (A) 1,6 Voltage (V) 146 Current (A) 1,6 Voltage (V) 150/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) Height of product, without chimney (mm) Height of the product Width of the product Minimum niche height On Minimum niche width On Minimum niche	Material body	Stainless steel	
Typology Wall-mounted Installation type Wall-mounted Type of control Mechanical Type of control Mechanical Type of control settings Decor panel options N/A Motor location Integrated motor in hood chimney Operating Mode Convertible Electrical connection rating (W) 146 Current (A) 1,6 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) 0 Height of product, without chimney (mm) 0 Height of the product 1150 Width of the product 450 Winimum niche height 0 Minimum niche height 0 Minimum niche width 0 Niche depth 10 Niche depth 10 Mechanical Machanical Mechanical Mechanical Minimum niche width 0 Mall-mounted Mall-mounted Mall-mounted Machanical Mechanical Minimum niche width 0	Colour chimney	Inox	
Installation type Type of control Type of control Settings Decor panel options Mode Integrated motor in hood chimney Operating Mode Electrical connection rating (W) Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Chimney height (mm) Height of product, without chimney (mm) Detail of the product Wild the product Minimum niche height Mode And Mechanical Mechanical Amendment of Mechanical Mechanical The Mechanical And Convertible Integrated motor in hood chimney Convertible Electrical connection rating (W) 146 Convertible Electrical connection rating (W) 146 146 146 146 150 150 150 150 150 150 150 15	Material chimney	Stainless steel	
Type of control Mechanical Type of control settings - Decor panel options N/A Motor location Integrated motor in hood chimney Operating Mode Convertible Electrical connection rating (W) 146 Current (A) 1,6 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) - Height of product, without chimney (mm) 0 Height of the product 1150 Width of the product 9898 Depth of the product 450 Minimum niche height 0 Minimum niche width 0 Niche depth 100 Niche depth 100 Mechanical Mechanical Mechanical Mechanical Acceptable Convertible Con	Туроlоду	Wall-mounted	
Type of control settings - Decor panel options N/A Motor location Integrated motor in hood chimney Operating Mode Convertible Electrical connection rating (W) 146 Current (A) 1,6 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) - Height of product, without chimney (mm) 0 Height of the product 1150 Width of the product 898 Depth of the product 450 Minimum niche height 0 Minimum niche height 0 Minimum niche width 0 Niche depth 10 Niche	Installation type	Wall-mounted	
Decor panel options N/A Motor location Integrated motor in hood chimney Operating Mode Convertible Electrical connection rating (W) 146 Current (A) 1,6 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) - Height of product, without chimney (mm) 0 Height of the product 1150 Width of the product 898 Depth of the product 450 Minimum niche height 0 Minimum niche width 0 Niche depth 0	Type of control	Mechanical	
Motor location Integrated motor in hood chimned Convertible Electrical connection rating (W) 146 Current (A) 1,6 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) - Schuko Chimney height of product, without chimney (mm) 0 Height of the product 1150 Width of the product 898 Depth of the product 450 Minimum niche height 0 Minimum niche width 0 Niche depth 0	Type of control settings	-	
Operating Mode Electrical connection rating (W) Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Chimney height (mm) Height of product, without chimney (mm) Height of the product Width of the product Width of the product Minimum niche height Minimum niche height Minimum niche width Niche depth Convertible 146 220-240 150 50/60 150 Schuko Schuko Chimney height (mm) 0 450 Minimum niche width 0 Niche depth	Decor panel options	N/A	
Electrical connection rating (W) 146 Current (A) 1,6 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) - Height of product, without chimney (mm) 0 Height of the product 1150 Width of the product 898 Depth of the product 450 Minimum niche height 0 Minimum niche width 0 Niche depth 0	Motor location	Integrated motor in hood chimney	
Current (A) 1,6 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) - Height of product, without chimney (mm) 0 Height of the product 1150 Width of the product 898 Depth of the product 450 Minimum niche height 0 Minimum niche width 0 Niche depth 0	Operating Mode	Convertible	
Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Schuko Chimney height (mm) Height of product, without chimney (mm) Height of the product Width of the product Width of the product Depth of the product Minimum niche height Niche depth O 220-240 50/60 150 Schuko Chimney height (mm) 0 450 Minimum niche width O Niche depth	Electrical connection rating (W)	146	
Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) - Height of product, without chimney (mm) 0 Height of the product 1150 Width of the product 898 Depth of the product 450 Minimum niche height 0 Minimum niche width 0 Niche depth 0	Current (A)	1,6	
Length of Electrical Supply Cord (cm) Plug type Schuko Chimney height (mm) Height of product, without chimney (mm) Height of the product Width of the product Baya Depth of the product Minimum niche height Niche depth 150 Schuko 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	Voltage (V)	220-240	
Plug type Chimney height (mm)	Frequency (Hz)	50/60	
Chimney height (mm) Height of product, without chimney (mm) Height of the product Width of the product Began Depth of the product Minimum niche height Minimum niche width O Niche depth	Length of Electrical Supply Cord (cm)	150	
Height of product, without chimney (mm) Height of the product Width of the product September 1150 Width of the product Winimum niche height Minimum niche width O Niche depth O	Plug type	Schuko	
Height of the product 1150 Width of the product 898 Depth of the product 450 Minimum niche height 0 Minimum niche width 0 Niche depth 0	Chimney height (mm)	-	
Width of the product 898 Depth of the product 450 Minimum niche height 0 Minimum niche width 0 Niche depth 0	Height of product, without chimney (mm)	0	
Depth of the product 450 Minimum niche height 0 Minimum niche width 0 Niche depth 0	Height of the product	1150	
Minimum niche height 0 Minimum niche width 0 Niche depth 0	Width of the product	898	
Minimum niche width 0 Niche depth 0	Depth of the product	450	
Niche depth 0	Minimum niche height	0	
·	Minimum niche width	0	
Net weight (kg) 18.3	Niche depth	0	
	Net weight (kg)	18.3	

TECHNICAL FEATURES		
Type of manual control devices	Buttons	
Type of automatic control devices	-	
Number of motors	1	
Total power of the motors (W)	140	
Number of speed settings: boost option availability	0	
Boost presence	No	
Maximum output air extraction (m³/h)	428	
Boost position air extraction (m³/h)	0	
Maximum output recirculating air (m³/h)	155	
Boost position output recirculating (m³/h)	0	
Light Control Type	On/Off	
Number of lights	2	
Type of lamps used	LED	
Total power of the lamps (W)	6	
Diameter of air outlet (mm)	150	
No-return airflow flap	No	
Grease filter material	Washable aluminium	
Odour filter	No	

PERFORMANCES	
Sound power at min. speed (2010/30/EU)	57
Sound power at max. speed (2010/30/EU)	65
Noise level with boost position (dB(A) re 1 pW)	0

