



Smartbright Waterproof G3 WTO 68C

WT068C CW LED56 L1500 PSU

Philips Smartbright Waterproof G3 batten offers exceptional value. It is perfect for everyday lighting installations. Available in three standard sizes, it has the option of standard and through-wiring versions.


Product data

General Information		Optical cover/lens material	
Light source colour	865 cool daylight	Optical cover/lens finish	Opal
Optical cover/lens type	No [-]	Overall length	1488 mm
Control interface	-	Overall width	69 mm
Protection class IEC	Safety class II (II)	Overall height	74 mm
CE mark	CE mark	Colour	White and grey
Number of products on MCB (16 A type B)	1		
Light source engine type	LED		
Operating and Electrical		Approval and Application	
Input Voltage	220 to 240 V	Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Input frequency	50 or 60 Hz	Mech. impact protection code	IK06 [1 J]
Power factor (min.)	0.9		
Controls and Dimming		Initial Performance (IEC Compliant)	
Dimmable	No	Initial luminous flux (system flux)	5600 lm
		Luminous flux tolerance	+/-10%
		Initial LED luminaire efficacy	110 lm/W
		Init. Corr. Colour Temperature	6500 K
		Init. Colour rendering index	>80
		Initial input power	51 W
Mechanical and Housing			
Housing material	Polycarbonate		

Smartbright Waterproof G3 WT0 68C


Power consumption tolerance	+/-10%
Application Conditions	
Ambient temperature range	-20 to +45 °C
Product Data	
Full product code	871016336061499
Order product name	WT068C CW LED56 L1500 PSU
EAN/UPC – product	8710163360614

Order code	36061499
SAP numerator – quantity per pack	1
Numerator – packs per outer box	12
SAP material	911401881580
SAP net weight (piece)	0.610 kg



Dimensional drawing

WT068C-5ft



WT068C CW LED56 L1500 PSU

