WR60 GGG 23125 XME





- Mechanical controls
- Inox Finishing
- Mirror glass door
- 4 gas burners
- Cavity capacity: 64 L
- Residual heat indicator
- Temperature range: 50-250 (°C)
- Electrical connection rating: 40 W
- 220-240 V
- 4 burners: 1 Rapid 3000 W burner, 1 Semirapid 2000 W burner, 1 Semirapid 2000 W burner, and 1 Auxiliary 1000 W burner.
- Adjustable feet
- 1 Rapid burner
- 1 Semirapid burner
- 1 Semirapid burner
- 1 Auxiliary burner
- Removable drawer/flap
- Dimensions (HxWxD): 850x600x600 mm

Whirlpool gas freestanding cooker: 60cm -WR60 GGG 23125 XME

This Whirlpool freestanding 60x60 Cooker features: inox color. Gas power supply. 4 gas burners. 60cm width.



Automatic Start

More simplicity in the use of your gas hob thanks to the two-handed ignition.



Multilevel Flame

10 intuitive pre-set flames for different cooking methods, reducing guesswork in the power selection.



Energy saving

Outstanding energy savings. Ovens with an A/ A+ energy rating offer an excellent level of energy efficiency, ensuring lower consumption and higher savings.



Stainless Steel

The elegance of this appliance's stainless steel design will make it the centrepiece of your kitchen.



Super Efficient Burners

The Super Efficient Burners provide outstanding cooking results, while effectively reducing gas consumption.



Core Design Line

Modern, innovative design, ideal for any kind of home environment, featuring comfortable protruding knobs an full glass door, to easily monitor your cooking.

WR60 GGG 23125 XME



| MAIN FEATURES | |
|--|---------------|
| Main colour of product | Inox |
| Construction type | Free-standing |
| Type of control | Mechanical |
| Type of control settings | - |
| Which kind of hobs can be controlled? | Gas |
| Number of gas burners | 4 |
| Gas connection | Cilindric |
| Number of electric cooking zones | 0 |
| Number of electric plates | 0 |
| Number of radiant plates | 0 |
| Number of halogen plates | 0 |
| Number of induction plates | 0 |
| Number of electric warming zones | 0 |
| Location of control panel | Front |
| Current (A) | 0,15 |
| Voltage (V) | 220-240 |
| Frequency (Hz) | 50/60 |
| Length of Electrical Supply Cord (cm) | 0 |
| Plug type | No |
| Height of the product | 850 |
| Width of the product | 600 |
| Depth of the product | 600 |
| Net weight (kg) | 48.5 |
| Usable volume (of cavity) - NEW (2010/30/EU) | 64 |
| Integrated Cleaning system | No |

| TECHNICAL FEATURES | | |
|---|-----|--|
| Timer | No | |
| Safety device | No | |
| | , | |
| PERFORMANCES | | |
| Energy input | Gas | |
| Type of energy of the cavity | Gas | |
| Energy consumption per cycle conventional - NEW (2010/30/EU) | 0 | |
| Energy consumption per cycle forced air convection - NEW (2010/30/EU) | 0 | |

