
CoreLine ProSet

CoreLine ProSet is a high quality 90mm downlight, offering superb lifetime of 50,000 hours, and IP44 rating so that it can be used in bathrooms as well as other typical residential and commercial applications. With adjustable ring, this product offers fantastic versatility to direct the light exactly where you want to put it. Consuming only 13W of energy, this product will deliver up to 75% energy savings, with even further savings possible through dimmability.



Features and Benefits

- Fit the application 3000K/ 4000K CCT, CRI80, high consistency
- Fixed and Adjustable fittings, white finish
- High Output 640lm output
- Saving Only 13W power consumption, vs 50W halogen
- Long lasting 50k hours lifetime vs 3k hours of halogen
- 90mm cutout Easily replace your halogen spotlight
- Plug and Play Prewired with 1.2m flex and 3-pin plug
- High compatibility Extensive leading edge dimmer compatibility list
- IP44 Applicable for Bathrooms



Product ID	Width (mm)	Height (mm)	Cut-out (mm)
RS121B	105	73	ø86

Dimensions in mm (Nominal)

CORELINE PROSET DOWNLIGHT		
Family Name	CoreLine ProSet Downlight	
Model	RSI2IB - Adjustable	
Lumen/ Watt	640lm/ I3W	
Lamp Colour	3000K, 4000K	
Colour Rendering Index (CRI)	80	
Flex and Plug	Yes	
Lifetime L70*	50,000 hrs	
Unified Glare Ratio (UGR)	n/a	
Optics	40D	
Driver	Integrated driver	

Dimmable	"Selected Leading edge dimmers. Please refer to www.philips.com.au for dimming details."
Installation	Recessed Adjustable
IP rating	IP44
Weight	RSI2IB - 0.33kg
Colour of housing	White
Application	Residential, Retail, Hospitality, Commercial
Accessories	NA
Suspension Height - min/max	NA
Maximum Run Length	NA
* = When the fitting reaches 709	6 of full potential (new)

RSI2IB LED6-40-/840 PSR WH CAU

911401575711

RSI2IBI3W4KDIM

RSI2IBI3W3KDIM 911401575511 RSI2IB LED6-40-/830 PSR WH CAU