


Master CDM-TD

CDM-TD range of double-ended, compact, high-efficiency, discharge lamps with a stable colour over lifetime and a crisp, sparkling light. UV-block for reduced health and fading risks. Direct retrofit in place for quartz metal halide lamps providing lower operating costs, reduced heat output, and better light quality.



| Product ID | Overall Length | Diameter | Light Centre Length | Arc Length |
|--------------|----------------|----------|---------------------|------------|
| | C max. | D max. | L nom. | O nom. |
| CDMTD70W830 | 119.63 | 22 | | 8 |
| CDMTD70W942 | 119.63 | 22 | | 7 |
| CDMTD150W830 | 137.43 | 25 | | 10 |
| CDMTD150W942 | 137.43 | 25 | | 10 |


Dimensions in mm

MASTER CDM-TD

| Shortcode | Description | Wattage (W) | Cap Base | Luminous Flux | Average Lifetime (hrs) | Colour Temp (K) | Min Order Quantity | Carton Qty |
|--------------|-------------------------------------|-------------|----------|---------------|------------------------|-----------------|--------------------|------------|
| CDMTD70W830 | MASTERC CDM-TD 70W/830 RX7s ICT/I2 | 70 | RX7s | 6500 | 15000 | 3000 | 1 | 12 |
| CDMTD70W942 | MASTERC CDM-TD 70W/942 RX7s ICT/I2 | 70 | RX7s | 6000 | 15000 | 4200 | 1 | 12 |
| CDMTD150W830 | MASTERC CDM-TD 150W/830 RX7s ICT/I2 | 150 | RX7s | 13250 | 15000 | 3000 | 1 | 12 |
| CDMTD150W942 | MASTERC CDM-TD 150W/942 RX7s ICT/I2 | 150 | RX7s | 14200 | 15000 | 4200 | 1 | 12 |

MHN-TD

High pressure quartz metal halide gas discharge lamps in a compact linear tube which offers high performance together with high colour rendering. MHN-TD lamps require control gear to operate and have a recommended burning position of ± 45 degrees from the horizontal.



| Product ID | Overall Length | Diameter | Light Centre Length | Arc Length | |
|------------|----------------|----------|---------------------|------------|--------|
| | C max. | D max. | L nom. | O nom. | B nom. |
| 70W | 139 | 24 | 64.9 | 17.8 | 132 |
| 150W | 139 | 24 | 64.9 | 17.8 | 132 |

Dimensions in mm

MHN-TD

| Shortcode | Description | Wattage (W) | Cap Base | Luminous Flux | Average Lifetime (hrs) | Colour Temp (K) | Min Order Quantity | Carton Qty |
|--------------|-----------------------------|-------------|----------|---------------|------------------------|-----------------|--------------------|------------|
| MHNTD70W730 | MHN-TD 70W/730 RX7s ICT/I2 | 70 | RX7s | 6200 | 9000 | 3000 | 1 | 12 |
| MHNTD70W842 | MHN-TD 70W/842 RX7s ICT/I2 | 70 | RX7s | 5700 | 10500 | 4200 | 1 | 12 |
| MHNTD150W730 | MHN-TD 150W/730 RX7s ICT/I2 | 150 | RX7s | 13800 | 10500 | 3000 | 1 | 12 |
| MHNTD150W842 | MHN-TD 150W/842 RX7s ICT/I2 | 150 | RX7s | 12900 | 10500 | 4200 | 1 | 12 |